"The Effect Of Various Polishing Systems On Surface Roughness Of Nano and Microhybrid Composite Restoratives : An In Vitro Surface Profilometric Study "

¹Dr.Smita Dutta,² Dr Rahul Maria.

ABSTRACT:

Introduction: The smoothness of the restorative material's surfaces have a great importance in the success and clinical longevity of the restorations.

Material & Methods: A total of 120 acrylic blocks with a recess of 2mm x 3mm x 3mm dimension were made using a custom made stainless steel template.(Figure 1) Of them, 60 specimens were of (microhybrid composite) and 60 were of (nano composite).

Results & Conclusion : From present study we were concluded Nanofilled composites (Supreme XT) showed better polish ability when compared with microhybrid composites (Filtex Z-250) with Mylar strip provide the smoothest surface finish for both supreme XT and Filtek Z-250.

Keywords: composites, surface roughness, polishability.

.....

INTRODUCTION : Use of synthetic resins in restorative dentistry has markedly increased in recent years due to increased demand of aesthetics¹. The surface quality is an important factor in determining the success of resin composite restorations. ² One of the most significant improvements is related to the use of nanotechnology.Nanofillers are described as "the discrete particles which have all of the three dimensions in the range of about 1-100nm".³The esthetic quality of a restoration may be as important to the mental health of the patient as the biological and technical qualities of

 Senior Lecturer
Professor and Head of the Department Dept of Conservative Dentistry And Endodontiocs.
Rishiraj Dental College and Research Centre Bhopal the restoration are to his physical and dental health⁴.Unfortunately, discoloration is still a problem for dental resin composite restorations. A survey of published studies indicated that smooth, highly polished restorations present a host of advantages as compared to restorations with a more roughened surface, ranging from esthetics to survival. They are more esthetically appealing and less susceptible to plaque accumulation and extrinsic discoloration. They exhibit improved mechanical properties⁵.

MATERIALS AND METHODS: This in-vitro study was conducted in the Department of Conservative Dentistry and Endodontics. A total of 120 acrylic blocks with a recess of 2mm x 3mm x 3mm dimension were made using a custom made stainless steel template.(Figure 1) Of them, 60 specimens were of (microhybrid composite) and 60 were of (nano composite).

To simulate initial finishing of the restorative material The remaining group were surfaced with a Diamond finishing bur in a rotary motion, for 15 seconds with water coolant. Group IB and IIB: 20 samples of each of the two composite resins were finished and polished with Optra-pol polishing system as specified by the manufacturer with application with light hand pressure using planar motion for 30seconds at 15,000 rpm, using slow speed handpiece Group IC and IIC: 20 samples of each of the two composite resins were finished and polished with the Sof-Lex system as specified by the manufacturer. After finishing and polishing, all the samples were subjected to Profilometric evaluation and surface roughness parameters (Ra) were recorded from the digital LCD read out. (Fig 2).

RESULTS:

Material	Ν	Mean	Std Deviation	
Z250	60	0.114	0.051	Student t test p = 0.003 Sig
Supreme XT	60	0.087	0.047	p = 0.000 015

Table 1: Showing mean surface roughness in two materials :

Table 1 shows the mean surface roughness between the two materials used. Supreme XT showed a mean surface roughness of 0.087 ± 0.047 and Z 250 showed a mean surface roughness of 0.114 ± 0.051 . The difference in mean was statistically significant as compared using student t test (p < 0.05).

Table 2a: Showing Mean surface roughness among different polishing systems with material Supreme XT

Polishing System	Ν	Mean	Std. Deviation	ANOVA
Mylar	20	0.041	0.020	p = 0.000 : Sig
Optra Pol	20	0.126	0.042	
Sof Lex	20	0.095	0.028	
Total	60	0.087	0.047	

Group	Compared to	Mean Difference	p value (Tukey test)	Sig
Mylar	Optra Pol	08481	.000	Sig
	Sof Lex	05333	.000	Sig
Optra Pol	Mylar	.08481	.000	Sig
	Sof Lex	.03148	.006	Sig
Sof Lex	Mylar	.05333	.000	Sig
	Optra Pol	03148	.006	Sig

Table 2b: Showing post op comparison between groups.

Table 2a shows the mean surface roughness between different polishing systems used with Supreme XT material. Mylar showed a mean surface roughness of 0.041 ± 0.020 , Optra Pol showed a mean surface roughness of 0.126 ± 0.042 and Z 250 showed a mean surface roughness of 0.095 ± 0.028 . The difference in mean was statistically significant as compared using ANOVA test (p < 0.05).

Table 2b shows showed significant difference in mean between the three groups. (p < 0.05)

Table 3a: Showing Mean surface roughness among different polishing systems with material Z 250

Polishing System	Ν	Mean	Std. Deviation	ANOVA
Mylar	20	0.056	0.026	p = 0.000 : Sig
Optra Pol	20	0.164	0.025	
Sof Lex	20	0.124	0.020	
Total	60	0.114	0.051	

Group	Compared to	Mean Difference	p value (Tukey test)	Sig
Mylar	Optra Pol	-0.108	0.000	Sig
	Sof Lex	-0.068	0.000	Sig
Optra Pol	Mylar	0.108	0.000	Sig
	Sof Lex	0.040	0.000	Sig
Sof Lex	Mylar	0.068	0.000	Sig
	Optra Pol	-0.040	0.000	Sig

Table 3b: Showing post hoc comparison between groups.

Table 3a shows the mean surface roughness between different polishing systems used with Z 250 material. Mylar showed a mean surface roughness of 0.056 ± 0.026 , Optra Pol showed a mean surface roughness of 0.164 ± 0.025 and Z 250 showed a mean surface roughness of 0.124 ± 0.020 . The difference in mean was statistically significant as compared using ANOVA test (p < 0.05).

DISCUSSION:

It is clinically important to determine the finishing technique that will result in the smoothest surface using minimum time and instruments Composite surface roughness is basically dictated by the size, hardness and amount of filler, all of which influence the mechanical properties of the resin composites, and by the flexibility of the finishing material, hardness of the abrasive and grit size⁶

It is known that surface roughness would harbor more bacteria leading to problems like excessive plaque accumulation, gingival irritation, increased surface staining, and poor or less than optimal esthetics of the restored teeth⁸.

The trimming procedure for resin- based restorations comprises four steps:

• Coarse finishing or reduction of excess: instruments with high grinding effectiveness are preferred but, due to the coarse abrasiveness, they should only be used on restorative material.

• Contouring: the aim to achieve final form of the restoration as prescribed by functional and aesthetic criteria.

• Fine finishing: this comprises the final, precise adjustment of restoration margins and improvement in surface smoothness.

• Polishing: a smooth and glossy, but nonetheless textured surface is the final objective of any polishing procedure⁹.

Group I (Nanocomposite Supreme XT) showed significantly smoother surface than Group II(Filtex-250 Microhybrid composite) with mean roughness value 0.087 for Group I and 0.114 for that of Group II. This is contributed to the fact that In addition to making possible the synthesis of nanosized filler particles, nanotechnology is believed to have a beneficial effect on the stable chemical integration of such particles within the composite matrix. This is thought to contribute to the low wear rates of nanoparticle composites. In the case of surface alteration caused by contact with abrasive polishing instruments, a surface that is composed of nanoparticles is less likely to suffer particle loss. This might explain the low surface roughness found on Supreme-XT specimens.11

M Jung et $al(2007)^{12}$ explained that in addition Solid filler particles in hybrid or microhybrid materials are considerably larger than nanosized particles. Another point which might be attributed good surface quality is the fact that to nanotechnology enables for obtaining high filler loading. Compared to microhybrid filtek-250, supreme-XT the nanocomposites had higher filler content by volume. Thus, it can be expected that, in nano composites, a greater number of particles will be present on the surface, establishing a larger contact area with rotating instruments. Moreover, the strong integration of nano particles within the composite material might further explain the results of this study. Mitra and others $(2003)^{13}$ assumed that, due to a strong chemical integration of nanoparticles into the resin matrix, nanocomposites wear by breaking off individual primary particles

rather than by breaking off larger particles, as with hybrid composites. This finding was supported by Turssi and others the authors reported that, in the case of Filtek Supreme, so-called nanoclusters were less prone to be sheared off during wear mechanisms.Even if it was possible, further contouring and finishing are usually required.¹⁴

In a similar study by Duygu Sarac et $al(2006)^{15}$ it was reported that lowest Ra values were obtained with the specimens polymerized against the polyester matrix group and while the aluminium oxide abrasive disc group showed lower Ra value than Optra-pol group For a composite finishing system to be effective the cutting particles (abrasive) must be relatively harder than the filler materials, otherwise the polishing agent will only remove a soft resin matrix and leave the filler particles protruding from the surface. The hardness of aluminium oxide is significantly higher than silicon dioxide, and generally, higher than most filler materials used in composite formulations. The trend of Sof-Lex discs is to provide a slightly smoother surface with the aluminium oxide abrasive on rigid matrix as this has the ability to flatten the filler particles and abrade the softer resin matrix at an equal rate. In the present study also Sof-Lex discs provided smoother surfaces than the optra-pol system.

It was shown that a greater number of polishing steps produced better smoothing effects. A multi-step system (soflex) achieved the best results; whereas, and one-step system (optra-pol) was consecutively less efficient, which is in accordance with the study done by M Jung et al (2007).¹² The multiple-step technique demonstrated to be most effective in obtaining a smoother surface, even for the microhybrid composite resin.

This fact can be explained by the operationalization of using these materials, as they are usually structured in sequential order of using with abrasiveness decreasing, favoring the final surface texture. This scenario does not occur with the one-step materials.

Group IB and IIB (The single-step system, Optra-pol) was used in the present study with no surface pretreatment. This system presented higher surface roughness values in comparison with the Group IC and IIC (Sof-Lex discs), regardless of the evaluated composite resin. Similar results were obtained by Yap et al (2004)¹⁷

According to Willems & others (1991) ¹⁸the inherent surface roughness of a restoration must be equal to lower than the surface roughness of enamel on enamel-to-enamel occlusal contact areas (Ra=0.64micron).⁸

A study by Kaplan and others $(1996)^{19}$ indicated that Ra values less than 10 µm are clinically Undetectable and, hence, any system that produces a surface roughness less than 10 µm is acceptable. With roughness values closer to 1 µm than to 10 µm, the polished specimens in this study showed acceptable surface finish.¹⁴

Aluminum oxide disks (Sof-Lex) are used to polish plane resin composite surfaces (Hondrum & Fernandez, 1997)²⁰, and they are particularly convenient for refining embrasure forms of posterior and anterior resin composite restorations.

In this invitro study, all systems were found to be effective in polishing the resin composite tested⁻ However Since there are several physiological and biological processes that may be related to the increase in the surface roughness, further studies are needed to determine which finishing techniques are best suited to clinical situations in which access is limited and restoration surface are complex. Therefore further studies should attempt to simulate concave and convex surfaces.²⁴

CONCLUSION : From present study we were concluded Nanofilled composites (Supreme XT) showed better polish ability when compared with microhybrid composites (Filtex Z-250) with Mylar strip provide the smoothest surface finish for both supreme XT and Filtek Z-250.

REFERENCES:

- R. Gupta et al; A Spectrophotometric Evaluation of Color Changes of Various Tooth Colored Veneering Materials after Exposure to Commonly Consumed Beverages; The Journal of Indian Prosthodontic Society ;2005;5:72-78.
- <u>Uçtaşli MB</u> et al; The Effect of Different Finishing and Polishing Systems on the Surface Roughness of Different Composite Restorative Materials; Journal of Contemporary Dental Practice;2007;8;2
- J Janus et al; Surface Roughness and Morphology of Three Nanocomposites after Two Different Polishing Treatments a Multitechnique Approach; Dental Materials,2010;26:416-.425
- **4.** Sturdevant's Art Science of Operative Dentistry,4th Edition,Roberson T.M,Heymann H.O.,Swift E.J,Mosby.
- Tatsuo ENDO et al; <u>Surface Texture and Roughness of</u> <u>Polished Nanofill and Nanohybrid Resin Composites</u>; 2010;29:213-223.
- Y Korkmaz et al; The Influence of One-step Polishing Systems on the Surface Roughness and Microhardness of Nanocomposites; Operative Dentistry, 2008, 33-1, 44-50.
- **7.** Ivo K Rejci et al; Resin Composite Polishing-Filling the Gaps; 1999; 30-7:490-495.
- I. E. Ruyter Composites -Characterization of Composite Filling Materials: Reactor Response ;Adv Dent Res 2-1:122-129.
- **9.** LS Turkun; the Effect of One-Step Polishing System on The Surface Roughness of Three Esthetic Resin Composite Materials ;Operative Dentistry;2004;29-2:203-211.

- 10 Michael Morgan: Finishing and Polishing of Direct Posterior Resin Restorations: Pract Proced Aesthet Dent 2004:16:211-216.
- 11 M Jung; Surface Geometry of Four Nanofiller and One Hybrid Composite after One-step and Multiplestep Polishing; Operative Dentistry, 2007, 32-4, 347-355.
- M Jung et al; Surface Texture of Four Nanofilled and One Hybrid Composite After Finishing; Operative Dentistry, 2007, 32-1, 45-52.
- Sumita B Mitra et al; An Application Of Nano Technology in Advanced Dental Materials;JADA;2003;134:1382-1390.
- AJ St Georges et al; Surface Finish Produced on Three Resin Composites by New Polishing Systems; Operative Dentistry;2005;30-5:593-597.
- Duygu Sarac et al; The Effect of Polishing Techniques on the Surface Roughness and Color Change of Composite Resins; J Prosthet Dent;2006;96:33-40
- Michael Morgan: Finishing and Polishing of Direct Posterior Resin Restorations: Pract Proced Aesthet Dent 2004:16:211-216
- A. U. J. Yap, S. H. Yap, C. K. Teo, and J. J. Ng, "Finishing/ polishing of composite and compomer restoratives: effectiveness of one-step systems," Operative Dentistry, vol. 29, no. 3, pp. 275–279, 2004
- G. Willems, P. Lambrechts, M. Braem', M. Vuylsteke-Wauters2, And G. Vanherle The Surface Roughness Of Enamel-To-Enamel Contact Areas Compared With The Intrinsic Roughness Of Dental Resin Compositesj Dent Res September 1991 70:1299-1305.
- Kaplan BA, Goldstein GR, Vijayaraghavan TV, Nelson IK. The effect of three polishing systems on the surface roughness of four hybrid composites: a profilometric and scanning electron microscopy study. J Prosthet Dent 1996; 76(1):34-8.

- Hondrum SO, Fernández R Jr. Contouring, finishing and polishing Class 5 restorative materials. Oper Dent 1997; 22: 30-36.
- Jung M, Voit S, Klimek J. Surface geometry of three packable and one hybrid composite after finishing. Oper Dent. 2003 Jan-Feb;28(1):53-9
- James W. Stoddard, D.D.S., Glen H. Johnson, D.D.S., M.S An evaluation of polishing agents for composite resins. The Journal of Prosthetic Dentistry Volume 65, Issue 4, April 1991, Pages 491–495
- Shintani H, Satou J, Satou N, Hayashihara H, Inoue The Effects of various finishing methods on staining and accumulation of Streptococcus mutans HS-6 on composite resins. Dent Mater. 1985 Dec;1(6):225-7.
- Rüstü Gedik; Surface Roughness of New Microhybrid Resin-Based Composites; J Am Dent Assoc 2005; 136; 1106-1112.

.....

Date of manuscript submission: 22 December 2011 Date of initial approval: 08 February 2012 Date of Peer review approval: 20 April 2012 Date of final draft preparation: 28 May 2012 Date of Publication: 9 June 2012 Conflict of Interest: Nil, Source of Support: Nil.

.....